

---

LEGGARI

# WB URETHANE MATTE

Part A Safety Data Sheet

---

## Table of Contents

Product Identification . . . . .	1
Hazard Identification . . . . .	2
Composition/Information on Ingredients . . . . .	3
First-aid Measures . . . . .	4
Fire-Fighting Measures . . . . .	5
Accidental Release Measures . . . . .	6
Handling and Storage . . . . .	7
Exposure Controls/Personal Protection . . . . .	8
Physical and Chemical Properties . . . . .	9
Stability and Reactivity . . . . .	10
Toxicological Information . . . . .	11
Ecological Information . . . . .	12
Disposal Considerations . . . . .	13
Transport Information . . . . .	14
Regulatory Information . . . . .	15
Other Information . . . . .	16



# 1 | PRODUCT IDENTIFICATION



**TRADE NAME (AS LABELED):**

**LEGGARI WB URETHANE MATTE PART A**

**SUPPLIER/MANUFACTURER'S NAME:**

**LEGGARI PRODUCTS, LLC**

**ADDRESS:**

**3105 E AINSWORTH AVE  
WAREHOUSE 5, BAY 2  
PASCO, WA 99301**

**TELEPHONE:**

**1-844-LEGGARI (534-4274)**

**EMAIL:**

**CUSTOMERSERVICE@LEGGARI.COM**

**GHS ratings**

Oral Toxicity:	Acute Tox. 4	Oral > 300 + ≤ 2000 mg/kg
Skin Corrosive:	3	Reversible adverse effects in dermal tissue, Draize score: ≥1.5 > 2.3
Skin Sensitizer:	1	Skin Sensitizer

**GHS hazards**

H302 - Harmful if swallowed

H316 - Causes mild skin irritation

H317 - May cause an allergic skin reaction

**GHS precautions**

P235 - Keep cool

P261 - Avoid breathing dust/fumes/gas/mist/vapors/spray

P264 - Wash thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P321 - Specific treatment (see ... on this label)

P330 - Rinse mouth

P363 - Wash contaminated clothing before reuse

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P302 + P352 - IF ON SKIN: Wash with soap and water

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention

P403 + P235 - Store in a well ventilated place. Keep cool

P501 - Dispose of contents/container to...

**Signal Word: warning**



Chemical Name	CAS number	Weight Concentration %
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	0.10% - 1.00%



## FIRST AID MEASURES FOR DIFFERENT EXPOSURE ROUTES

### **Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

### **Eye contact**

Immediately flush eyes with plenty of water for least at 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

### **Skin contact**

Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

### **Ingestion**

If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cups full of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

### **Aspiration hazard**

Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

**Extinguishing media**

Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical and Water Fog.

**Unusual fire and explosion hazards**

No unusual fire or explosion hazards noted. Keep containers tightly closed.

**Special firefighting procedures**

Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.



## **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES**

### **For non-emergency personnel**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### **For emergency responders**

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Precaution for Safe Handling**

Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**Conditions for Safe Storage**

Keep from freezing. Store in a dry, well ventilated place. Keep container tightly closed when not in use.





Chemical / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Distillates, petroleum, solvent-refined heavy paraffinic 64741-88-4	Not Established	Not Established	Not Established

## INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

### **Engineering controls**

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

### **Respiratory protection**

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

### **Skin protection**

Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

### **Eye protection**

Use safety eye wear designed to protect against splash of liquids.

### **Other protective equipment**

Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

### **Hygienic practices**

Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.



<b><u>Appearance:</u></b>	Liquid, Milky
<b><u>Odor:</u></b>	Mild
<b><u>Odor threshold:</u></b>	N/A
<b><u>PH:</u></b>	N/A
<b><u>Melting point:</u></b>	N/A
<b><u>Boiling point:</u></b>	212 °F (100°C)
<b><u>Flash Pt (F/C):</u></b>	N/A
<b><u>Evaporation rate:</u></b>	N/A
<b><u>Flammability (solid, gas):</u></b>	0.38
<b><u>LEL/UEL:</u></b>	N/A
<b><u>Vapor Pressure:</u></b>	N/A
<b><u>Vapor density:</u></b>	3.8
<b><u>Relative density:</u></b>	1.05
<b><u>Solubility:</u></b>	Dilutable
<b><u>Partition coefficient-</u></b>	
<b><u>Octanol/water:</u></b>	N/A
<b><u>Autoignition temp:</u></b>	N/A
<b><u>Decomposition temp:</u></b>	N/A
<b><u>Viscosity:</u></b>	N/A



### **Conditions to avoid**

Avoid contact with strong acid and strong bases.

### **Hazardous decomposition**

By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

### **Hazardous polymerization**

Will not occur under normal conditions.

### **Stability**

This product is stable under normal storage conditions.

### **Incompatibility**

Incompatible with strong oxidizing agents, strong acids and strong alkalis.



## MIXTURE TOXICITY

### COMPONENT TOXICITY

64741-88-4

-Distillates, petroleum, solvent-refined heavy paraffinic  
Inhalation LC50: 2 mg/L (Rat)

## EXPOSURE TO THIS MATERIAL MAY AFFECT THE FOLLOWING ORGANS:

### EFFECTS OF OVEREXPOSURE

#### **Eye contact**

Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

#### **Skin contact**

Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

#### **Inhalation**

Low hazard for usual industrial handling or commercial handling by trained personnel. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

#### **Ingestion**

Substance may be harmful if swallowed.

#### **Primary Route(s) of entry**

Eye contact, ingestion, inhalation, skin absorption and skin contact.



## COMPONENT ECOTOXICITY:

Distillates, petroleum, solvent-refined  
heavy paraffinic -

96 Hr LC50 Oncorhynchus mykiss: > 5000 mg/L  
48 Hr EC50 Daphnia magna: > 1000 mg/L



## **DISPOSAL INFORMATION:**

Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.



## THIS MATERIAL IS CLASSIFIED FOR TRANSPORT AS FOLLOWS:

**Agency:** DOT  
**Proper Shipping Name:** Non-Regulated Material  
**UN Number:** -  
**Packing Group:** -  
**Hazard Class:** -



**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!**

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

**CERCLA-SARA Hazard Category:**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

- None

**Sara Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

- None





## HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)

<b>HEALTH</b>	1
<b>FLAMMABILITY</b>	1
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X

HMIS & NFPA Hazard Rating Legend

\* = Chronic Health Hazard

**0 = Insignificant**

**1 = Slight**

**2 = Moderate**

**3 = High**

**Prepared by:**

**LEGGARI PRODUCTS LLC**

**Revision Date:**

**JANUARY 2022**

### DISCLAIMER:

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.