
LEGGARI

WB URETHANE

Part B Safety Data Sheet

Table of Contents

Product Identification	1
Hazard Identification	1
Composition/Information on Ingredients	1
First-aid Measures	2
Fire-Fighting Measures	2
Accidental Release Measures	2-3
Handling and Storage	3
Exposure Controls/Personal Protection	3-4
Physical and Chemical Properties	4
Stability and Reactivity	4-5
Toxicological Information	5
Ecological Information	5
Disposal Considerations	5
Transport Information	6
Regulatory Information	6
Other Information	6



1 | PRODUCT IDENTIFICATION



TRADE NAME (AS LABELED): LEGGARI WB URETHANE PART B

SUPPLIER/MANUFACTURER'S NAME: LEGGARI PRODUCTS LLC

ADDRESS: 3105 E AINSWORTH AVE
WAREHOUSE 5, BAY 2
PASCO, WA 99301

TELEPHONE: 1-844-LEGGARI (534-4274)

EMAIL: CUSTOMERSERVICE@LEGGARI.COM

EMERGENCY NUMBER: 800-424-9300

2 | HAZARD(S) IDENTIFICATION



GHS ratings

Inhalation Toxicity:	Acute Tox 4.	Gases > 2500 + ≤ 5000 ppm, Vapors >10 + ≤20 mg/l, Dusts & mists >1 + ≤5mg/l
Skin Sensitizer:	1	Destruction of dermal tissue: Exposure < 1 hour Observation < 14 days, visible necrosis in at least one animal
Organ toxin single exposure	3	Transient target organ effects - Narcotic effects - Respiratory tract irritation

GHS hazards

H317 - May cause an allergic skin reaction
H332 - Harmful if inhaled
H335 - May cause respiratory irritation

GHS precautions

P261 - Avoid breathing dust/fumes/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P363 - Wash contaminated clothing before reuse
P302 + P352 - IF ON SKIN: Wash with soap and water
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention
P405 - Store locked up
P403 + P233 - Store in a well ventilated place. Keep container tightly closed
P501 - Dispose of contents/container to...

SIGNAL WORD: WARNING



3 | COMPOSITION/INFORMATION ON INGREDIENTS



Chemical Name	CAS number	Weight Concentration %
Hexamethylene diisocyanate homopolymer	28182-81-2	70.00% - 80.00%
Cyclohexanamine, N,N-dimethyl-, compounds with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	666723-27-9	10.00% - 20.00%





FIRST AID MEASURES FOR DIFFERENT EXPOSURE ROUTES

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Ingestion

If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cups full of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

Aspiration hazard

Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

Skin contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

Eye contact

Immediately flush eyes with plenty of water for least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

5 | FIRE FIGHTING MEASURES



Extinguishing media

Use dry chemical, CO₂, Water spray (fog) or foam.

Unsuitable Extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground.

- Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide, carbon monoxide, nitrogen oxides.

Special protective actions for fire fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 | ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".



METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, watercourses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7 | HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING

Protective measures

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Approach release from upwind. Prevent entry into sewers, watercourses, basements or confined areas.

Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

8 | EXPOSURE CONTROLS/PERSONAL PROTECTION



Chemical / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Hexamethylene diisocyanate homopolymer 82182-81-2	Not Established	Not Established	Not Established
Cyclohexanamine, N,N-dimethyl-, compounds with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer 666723-27-9	Not Established	Not Established	Not Established

Appropriate Engineering Controls:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to



airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

General hygiene considerations

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Hands Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Other Skin Protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Eye/Face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

BODY PROTECTION:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

9 | PHYSICAL AND CHEMICAL PROPERTIES



Appearance:	Liquid, light yellow	Vapor Pressure:	HDI Polyisocyanate: 5.2 X 10 ⁻⁹ @ 68°F (20°C) mmHg
Odor:	Slight	Vapor density:	N/A
Odor threshold:	N/A	Relative density:	Approximately 1.15 @ 20°C (68°F)
PH	N/A	Solubility:	Insoluble - Reacts slowly with water to liberate CO ₂ gas
Melting point:	N/A	Partition coefficient-	
Boiling point:	Decomposition	Octanol/water:	N/A
Flash Pt (F/C):	ca. 365°F (185°C) (DIN EN 22719)	Autoignition temp:	ca. 833°F (445°C) (DIN 51794)
Evaporation rate:	N/A	Decomposition temp:	ca. 357.8°F (181°C)
Flammability (solid, gas):	N/A	Viscosity:	Approximately 800 mPa.s @ 68°F (20°C)
LEL/UEL:	N/A		

10 | STABILITY AND REACTIVITY



Conditions to avoid

Avoid all possible sources of ignition. Avoid temperatures above 120 °F. Avoid contact with strong acid and strong bases.



Incompatibility

Incompatible with strong oxidizing agents, strong acids and strong alkalis.

Hazardous decomposition:

By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents, which may form carbon monoxide, carbon dioxide, and formaldehyde.

Hazardous polymerization:

Will not occur under normal conditions.

Stability:

This product is stable under normal storage conditions.

11 | TOXICOLOGICAL INFORMATION

**MIXTURE TOXICITY**

Inhalation toxicity LD50: 23mg/L

COMPONENT TOXICITY**EXPOSURE TO THIS MATERIAL MAY AFFECT THE FOLLOWING ORGANS:****Effects of Overexposure:****Inhalation**

Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Eye contact

Causes serious eye irritation.

Ingestion

Irritating to mouth, throat and stomach.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS**Eye contact**

Adverse symptoms may include the following: pain or irritation, watering, redness.

Inhalation

Adverse symptoms may include the following: respiratory tract irritation, coughing, wheezing, and breathing difficulties-asthma.

Skin contact

Adverse symptoms may include the following: irritation, redness.

Ingestion

No specific data.

12 | ECOLOGICAL INFORMATION

**COMPONENT ECOTOXICITY:**

None

13 | DISPOSAL CONSIDERATION

**WASTE DISPOSAL METHODS:**

Dispose of material in compliance with all local, state and federal government regulations.





THIS MATERIAL IS CLASSIFIED FOR TRANSPORT AS FOLLOWS:

Agency: DOT
Proper Shipping Name: Non-Regulated Material
UN Number: -
Packing Group: -
Hazard Class: -



State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:
 - None

CERCLA-SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
 - None

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:
 - None



HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	1
PERSONAL PROTECTION	X

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazards
 0 = Insignificant
 1 = Slight
 2 = Moderate
 3 = High

PREPARED BY:
REVISION DATE:

Leggari Products LLC
 January 1, 2023

DISCLAIMER:

Leggari Products, LLC believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Leggari Products, LLC makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

